

EPT - 20 - 20A

Electric Pallet Truck

	Model			EPT - 20 - 20A	
				540	685
1	Characteristics	Capacity	Kg	2000	
2		Load center	mm	600	
3		Power device		Battery	
4		Operator type		Rider	
5		Wheel (Drive / Load)		Polyurethane / Polyurethane	
6		Wheel quantity		1D + 4L / 1D + 2L	
7	Specifications	Max. speed	Laden Unladen	Km/h	6 8
8		Max. lifting speed	Laden Unladen	m/s	0.056 0.060
9		Max. lowering speed	Laden Unladen	m/s	0.057 0.059
10		Gradeability	Laden Unladen	%	5 7
11	Dimensions	Lifting height	h	mm	120
12		Ground clearance + fork thickness	h1	mm	85
13		Raised height	h2	mm	205
14		Height rider platform	h3	mm	240
15		Height from ground to instrument face	h4	mm	870
16		Fork thickness	S	mm	55
17		Overall length	L	mm	2077
18		Fork length	L1	mm	1150
19		Body length	L2	mm	927
20		Overall width	B	mm	802
21		Overall fork width	B1	mm	540
22		Size of load wheel	D1	mm	Ø 80 × 120(single wheel) Ø 80 × 80(double wheel)
23		Size of steering wheel	D2	mm	Ø 248 × 65
24		Size of balance wheel		mm	Ø 138 × 68
25		Min. Outside turning radius	Wa	mm	1872
26	Driving system	Fork width	e	mm	185
27		Aisle width (800 × 1200mm pallet);vertical/horizontal	Ast3	mm	1630
28		Aisle width (1000 × 1200mm pallet);vertical/horizontal	Ast3	mm	1838
29		Max. Battery size(L×W×H)		mm	608 × 274 × 480
30		Battery type			Industry
31	Driving system	Voltage / Capacity	V / Ah		24 / 210
32		Driving motor	kw		2.2
33		Lifting motor	kw		2
34		Control system			CURTIS 1243
35		Traveling brake			Regenerate
36		Brake			Electromagnetic

